


114W / 114T (TURBO)

WASSERGEKÜHLTER INDUSTRIEMOTOR MIT
DIREKTER KRAFTSTOFF-EINSPRITZUNG

INDUSTRIAL DIESEL ENGINE
WITH DIRECT INJECTION





115 W

**BOOTS MOTOR MIT GETRIEBE UND
INDIREKTER KRAFTSTOFF-EINSPRITZUNG**

**MARINE DIESEL INCLUDING GEARBOX
WITH INDIRECT INJECTION**



TECHNICAL INFORMATION

Application

Useful for the repair of cracks in concrete and masonry. It is also used for the repair of concrete and masonry in the vicinity of walls and ceilings in residential buildings.

Preparation

Remove loose material, clean and dry. Apply to a depth of 20 mm into the crack.

Method

Apply with a brush or trowel. Do not over-apply.

How to use

Apply to the surface of the crack.

Notes

Do not use on wet surfaces.

Use

For the repair of cracks in concrete and masonry.

Notes

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

Do not use on wet surfaces.

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

TECHNICAL INFORMATION

Application

Useful for the repair of cracks in concrete and masonry. It is also used for the repair of concrete and masonry in the vicinity of walls and ceilings in residential buildings.

Preparation

Remove loose material, clean and dry. Apply to a depth of 20 mm into the crack.

Method

Apply with a brush or trowel. Do not over-apply.

How to use

Apply to the surface of the crack.

Notes

Do not use on wet surfaces.

Use

For the repair of cracks in concrete and masonry.

TECHNICAL INFORMATION

Notes

Do not use on wet surfaces.

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

Notes

Do not use on wet surfaces.

TECHNICAL INFORMATION

Application

Useful for the repair of cracks in concrete and masonry. It is also used for the repair of concrete and masonry in the vicinity of walls and ceilings in residential buildings.

Preparation

Remove loose material, clean and dry. Apply to a depth of 20 mm into the crack.

Method

Apply with a brush or trowel. Do not over-apply.

How to use

Apply to the surface of the crack.

Notes

Do not use on wet surfaces.

Use

For the repair of cracks in concrete and masonry.

Notes

Do not use on wet surfaces.

