

ISUZU INDUSTRIAL DIESEL MODEL 6BG1T

Main Specifications

Type	6Cylinder, Turbodiesel, water cooled, 100°
	Variable Valve, Diesel Injection, Turbocharged
Bore & Stroke	4.1 x 4.6 (161 mm x 181 mm)
Rated Output	296.7 cv (215 hp)
Dry Weight	1,104 kg
Dimensions - L x W x H	48.7 x 77.0 x 77.0 cm
Coolant Capacity (Water)	18.7 lps
Crude Oil Capacity	16.4 lps (34.0 qt)
Injection System	Common rail diesel flow controlled
Compression Ratio	17.5
2 year/2000 hour warranty, parts & labor, for the Operator	

Standard Features

Aluminum	Cast iron
Valve Regulator	Integral CR
Water	CR - 100%
Hydraulic Steering	14.8 lps
Hydrolic	0.7 lps
Air Intake	Intercooler - Water
Exhaust System	Variable - water
Oil Pan	Cast iron, 16 liters (4.2 gal)
Fuel	25.0 lps (5.3 gal) consumption
Oil Filter	Full Flow - 40 PPM

Industrial Rating

Maximum	1700 RPM @ 1000000
Continuous	1500 RPM @ 1000000
Maximum Torque	4200 Nm @ 1500 RPM

6P4 Coupled



Some options may be shown



Isuzu Diesel Engines
20000000
10000000
10000000
10000000
10000000
10000000



Subject to change without prior notice

ISUZU INDUSTRIAL DIESEL MODEL 6BG1T

Special Features

Direct injection
Glow plug starting system
Repairable-by-tool
Oil cooled piston

Dimensions



2 year/2000 hour warranty* including parts & labor

for parts



Dealership Name: Engle
1800 Westline
P.O. Box 101
Canton, OH 44702
Tel: 330.938.3300
Fax: 330.938.3300

Dealership slogan: making progress



isuzu.com