

Lombardini Four Cylinders Engines



L54

4

650

620

1100

1100 : 1

1100

20.7 / 30.0

20.0 / 40.0

10.00 ⌀ 1000

6.000 ⌀ 1200

100 ⌀ 1400

20

0.100

0.00



Lombardini Four Cylinders Motors



120

4

100

75

310

17.5/1.1

60.7 / 60.3 (3) 3000

60.7 / 60.3 (3) 3000

60.7 / 64.3 (3) 3000

10.00 (3) 3000

5.00 (3) 3000

11.5 (3) 3000

10

0.120

7

2.0





LOMBARDINI

BIOSCOLO & STRATTON
Lombardini Diesel, Inc.
2400 Lombard Avenue, St. Louis,
Missouri 63104-2470, U.S.A. Telex: 510101 LOMBAR

5LD930-4



60 HP (44 kW) (DIN)

1500-2000 RPM



GROUP 5L

Specificaciones técnicas y precios en español

Model	5LD-930-4	
Cylinder	4	
Bore	72.0 mm	2.835 in
Stroke	72.0 mm	2.835 in
Displacement	260.2 cm ³	15.86 cu in
Compression ratio	16.0	
Max. RPM	2000	
Power (kW)	1500 RPM	31.1 (42.5) HP
	1800 RPM	41
	2000 RPM	44
Max. Torque	140 kgm	13.72 ft-lb
Compression	1.6 (16.0)	1.6 (16.0)
Injection	1.6 (16.0)	1.6 (16.0)
Injection	1.6 (16.0)	1.6 (16.0)
Stroke	72.0 mm	2.835 in

STANDARD INDUSTRIAL SPEC.

This unit meets diesel engine test criteria shown in table below. Engine torque, power and performance data shown in table below. Other engine specifications are shown in separate technical literature. For further information, contact your local distributor or write to: Lombardini Diesel, Inc., 2400 Lombard Avenue, St. Louis, Missouri 63104-2470, U.S.A.

DIE FURTHER

1. SUBSTITUTION ENGINE INFORMATION AND SPECIFICATIONS: Many units are used.
2. SERVICE AND MAINTENANCE INFORMATION: See literature for only use correct service parts and.
3. SPECIFIC DIESEL ENGINE INFORMATION: See literature for complete information on engine specifications. (Detailed information on the 5LD-930-4 engine is available from Lombardini Diesel, Inc., 2400 Lombard Avenue, St. Louis, Missouri 63104-2470, U.S.A. For more information, contact your local distributor or write to: Lombardini Diesel, Inc., 2400 Lombard Avenue, St. Louis, Missouri 63104-2470, U.S.A.)
4. SERVICE: See the correct engine operation manual, correct literature.